11502
LORAN-C OVERPRINTED

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

Nautical Miles 1 ½ 0 1 2 3 4 5 6 7
Yards 1000 0 5000 10000

Formerly C&GS 1242, 1st Ed., June 1927 C-1940-524

This nautical chart has been designed to promote safe navigation. The National Ocean Survey encourages users to submit corrections, additions, or comments for improving this chart to the Director, National Ocean Survey, NOAA, Rockville, Maryland 20852.

SOUNDINGS IN FEET

Nautical Chart Catalog No. 1, Panels A,Q,R

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 4 for important supplemental information.

NOTE S
Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

UNITED STATES – EAST COAST
GEORGIA – FLORIDA

DOBOY SOUND TO FERNANDINA

Mercator Projection
Scale 1:80,000 at Lat. 31°02'
North American 1927 Datum
SOUNDINGS IN FEET
AT MEAN LOW WATER

For Symbols and Abbreviations see Chart No. 1
COLREGS: International Regulations for Preventing Collisions at Sea, 1972
Demarcation lines are shown thus: — — — —

HEIGHTS
Heights in feet above Mean High Water.

AUTHORITIES
Hydrography and topography by the National Ocean Survey with additional data from the Corps of Engineers and U.S. Coast Guard.

TIDAL INFORMATION

Place	Height referred to datum of soundings (MLW)			
	Mean High Water	Mean Tide Level	Mean Low Water	Extreme Low Water
	feet	feet	feet	feet
Sapelo Island				
Doboy Sound	6.8	3.4	0.0	−3.5
St. Simons Light	6.6	3.3	0.0	−3.5
Brunswick, East River	7.3	3.6	0.0	−3.5
Jekyll Point,				
St. Andrews Sd.	6.6	3.3	0.0	−3.5
St. Marys entrance,				
North Jetty	5.8	2.9	0.0	−3.5
Fernandina Beach,				
Amelia R.	6.0	3.0	0.0	−4.0

(881)

INTRACOASTAL WATERWAY
Use charts Nos 11507 and 11489
The depths and channel markers are not shown hereon

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 4, or weekly Notice to Mariners which include new or revised regulations. Information concerning the regulations may be obtained at the Office of the District Engineer, Corps of Engineers in Jacksonville, Fl. and Savannah, Ga.
Anchorage regulations may be obtained at the Office of the Commander, 7th Coast Guard District in Miami, Florida.
Refer to section numbers shown with area designation.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart.
See Notice to Mariners.

CAUTION
Only marine radiobeacons have been calibrated for surface use. Limitations on the use of certain other radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and Defense Mapping Agency Hydrographic/Topographic Center Publication 117 (A & B).
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

NOAA VHF-FM WEATHER BROADCASTS
The National Weather Service stations listed below provide continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.
Jacksonville, Fla. KHB-39 162.55 MHz

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOTE B
CAUTION
The entrance to St. Andrew Sound is subject to frequent change. Buoys 3, 5, 7 and 9 are not charted as they are frequently shifted in position.

NOTE C
The buoys marking these fish havens are not charted.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

LORAN-C
GENERAL EXPLANATION

LORAN-C FREQUENCY ..... 100kHz.
PULSE REPETITION INTERVAL
7980 ..... 79,800 Microseconds
STATION TYPE DESIGNATORS: (Not individual station letter designators).
M ..... Master
W ..... Secondary
X ..... Secondary
Y ..... Secondary
Z ..... Secondary
EXAMPLE: 7980-Y

RATES ON THIS CHART
7980-Y 7980-Z

The Loran-C lines of position overprinted on this chart have been prepared for use with ground wave signals and are presently compensated only for theoretical propagation delays which have not yet been verified by observed data. Mariners are cautioned not to rely entirely on the lattices in inshore waters. Skywave corrections are not provided.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

NOTE X
TERRITORIAL SEA AND CONTIGUOUS ZONE
The lines delimiting the territorial sea and contiguous zone represent an interdepartmental committee's interpretation of legal principles as applied to geographical information. The lines are subject to revision when required by correction of the geographic information shown or by reinterpretation of the legal principles involved. Where differences occur between adjacent or overlapping charts, the lines shown on the most recent chart issue take precedence.

Published at Washington, D. C.
U. S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SURVEY

FILE COPY

LITHOGRAPHIC COPY

19th Ed., Sept. 18/82 ■
11502
LORAN-C OVERPRINTED

CAUTION
This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the print date shown in the lower left hand corner.

SOUNDINGS IN FEET

FATHOMS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
FEET 6 12 18 24 30 36 42 48 54 60 66 72 78 84 90 96 102
METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

(Doboy Sound to Fernandina)
SOUNDINGS IN FEET - SCALE 1:80,000

11502
LORAN-C OVERPRINTED

DMA STOCK NO. 11BCO11502