NAUTICAL CHART
12372
MERCATOR PROJECTION AT SCALE 1:40,000
SOUNDINGS IN FEET AT MEAN LOW WATER
NORTH AMERICAN 1927 DATUM
HEIGHTS
Heights in feet above Mean High Water
AUTHORITIES
Hydrography and topography by the National Ocean Survey (formerly the Coast and Geodetic Survey) with additional data from the Corps of Engineers and U.S. Coast Guard.
SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 2 for important supplemental information
For Symbols and Abbreviations See Chart No. 1
COLREGS: International Regulations for Preventing Collisions at Sea, 1972. Demarcation lines are shown thus: – – – – –
CAUTION
This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the print date shown in the lower left hand corner.
Published at Washington, D. C.
U. S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SURVEY
NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 2, or weekly Notice to Mariners which include new or revised regulations. Information concerning the regulations may be obtained at the Office of the Division Engineer, Corps of Engineers in Waltham, Mass.
Anchorage regulations may be obtained at the Office of the Commander, 3rd Coast Guard District in New York, N.Y.
Refer to section numbers shown with area designation.
POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).
NIANTIC RIVER
Sandy Point
Oswegatchie
Keeny Cove
SCALE 1:20,000
NAUTICAL MILES
YARDS
WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.
Gorton Pond
Saunders Point
Clark Pond
Pine Grove
Bush Pond
Dodge Pond
NIANTIC RIVER AND SMITH COVE
Aids are privately maintained
NIANTIC
NIANTIC RIVER
The controlling depths were 7 feet for a width of 100-50 feet from the channel entrance 41°19′10″N., 72°10′55″W.) to the highway swing bridge, thence 5 feet for a width of 100 feet to Daybeacon 31.
May 1978
McCook Pt
Wigwam Rk
Patagansett River
Crescent Beach
Crescent Park
Indian Pond
Threefoot Rk
Waterford I
Black Rk
NIANTIC BAY
JOINS NORWICH EXTENSION BELOW
SAND PIER
Fl 2.5sec 24ft "37"
CAUTION
The dikes along the Thames River from Easter Point to Norwich are submerged at half tide.
Trading Cove
PERCHE ROCK
Fl 4sec 24ft "33"
Rolling Mill Dike
Long Rock Dike
BURNT HOUSE PIER
Fl R 4sec 24ft "32"
PRIDE PIER
Fl R 4sec 21ft "30"
Trading Cove Dike
FIXED BRIDGE HOR CL 10 FT VERT CL 5 FT
STANDPIPE
THAMES RIVER
The controlling depths at MLW were 23.3 feet for a mid-width of 100 feet or 16.0 feet for a 200 foot width from the north end of the turning basin east of Smith Cove to Stoddard Hill; thence 18.6 feet for a width of 200 feet to the basin at Norwich and 11.0 feet in the turning basin.
Aug-Sept 1974
Poquetanuck Cove
POQUETANUCK EXTENSION
RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.
INDIAN HILL
Fl 4sec 9ft "29"
Pennimar Reef
F R (Priv maintd lts)
Fort Pt
NORWICH
Yantic River
Shetucket R
Laurel Hill
Thamesville
LOWER COAL DOCK
Fl R 4sec 15ft "40"
Thames River
NORWICH EXTENSION
Mohegan
Easter Pt
Massapeag
Stoddard Hill
THAMES RIVER
LONG REACH UPPER
LONG REACH LOWER
SCALE 1:20,000
NAUTICAL MILES
YARDS
OVERHEAD POWER CABLE AUTHORIZED CL 17 FT
THAMES RIVER EXTENSION
JOINS POQUETANUCK EXTENSION ABOVE
JOINS EXTENSION AT LEFT
THAMES RIVER
The controlling depths at MLW were 23.3 feet for a mid-width of 100 feet or 16.0 feet for a 200 foot width from the north end of the turning basin east of Smith Cove to Stoddard Hill; thence 18.6 feet for a width of 200 feet to the basin at Norwich and 11.0 feet in the turning basin.
Aug-Sept 1974
OVERHEAD POWER CABLE AUTHORIZED CL 17 FT
Kitemaug
Montville Sta
Gales Ferry
Yale Boathouse
Bartlett
Harvard Boathouse
Cow Pt
Long Cove
NOTE B
Corps of Engineers authorized project depths are 20 feet for width of 350 ft. in westerly channel and 25 feet for width of 250 ft. in easterly channel. Widths from 410 ft. to 1020 ft. are provided by the U.S. Navy.
Platforms
SCALE 1:20,000
NAUTICAL MILES
YARDS
SECURITY ZONE C
127.305 (see note A)
Smith Cove
Mamacoke Hill
THAMES RIVER
NEW LONDON
GROTON
NEW LONDON HARBOR
SECURITY ZONE A
Jacobs Rock
Bailey Pt
GREENS HARBOR
Buoys 5, 6, & 7 are privately maintained
INSET 1
GENERAL ANCHORAGE
JOINS EXTENSION AT RIGHT
North Cove
ESSEX
Middle Cove
Thatchbed Island
SPEC ANCH 110.1 & 110.55
South Cove
Nott I
Hamburg
Hamburg Cove
Lord Cove
Goose I
CONNECTICUT RIVER
NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 2, or weekly Notice to Mariners which include new or revised regulations. Information concerning the regulations may be obtained at the Office of the Division Engineer, Corps of Engineers in Waltham, Mass.
Anchorage regulations may be obtained at the Office of the Commander, 3rd Coast Guard District in New York, N.Y.
Refer to section numbers shown with area designation.
ANCHORAGE AREAS
110.147 (see note A)
(A) NAVAL ANCHORAGE -
(B) GENERAL ANCHORAGE
Ferry Pt
STORM WARNINGS
SCALE 1:20,000
NAUTICAL MILES
YARDS