COLREGS, 80.145 (see note A)
International Regulations for Preventing Collisions at Sea, 1972.
The entire area of this chart falls seaward of the COLREGS Demarcation Line.

LOGARITHMIC SPEED SCALE

1 2 3 4 5 6 7 8 9 10 15 20 25 30 40 50 60

To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is16.0 knots

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 2. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 1st Coast Guard District in Boston, Mass., or at the Office of the Division Engineer, Corps of Engineers in Waltham, Mass.
Refer to charted regulation section numbers.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910 - 3282.

SOUNDINGS IN FEET

Nautical Chart Catalog No. 1, Panel G

13219

Formerly C&GS 268 1st Ed., Mar. 1953 D-1953-822

NOAA — NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION — U.S. DEPARTMENT OF COMMERCE — COAST SURVEY

UNITED STATES — EAST COAST

RHODE ISLAND

POINT JUDITH HARBOR

Mercator Projection
Scale 1:15,000 at Lat. 41°23′
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

TIDAL INFORMATION

Place Name (LAT/LONG)	Height referred to datum of soundings (MLLW) Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
	feet	feet	feet	feet
Point Judith Harbor of Refuge (41°22′N/71°29′W)	3.4	3.2	0.1	-3.0

(293) Latest information available.

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical; Al alternating; B black; Bn beacon; C can; DIA diaphone; F fixed; Fl flashing; G green; IQ interrupted quick; Iso isophase; LT HO lighthouse; M nautical mile; m minutes; MICRO TR microwave tower; Mkr marker; Mo morse code; N nun; OBSC obscured; Oc occulting; Or orange; Q quick; R red; Ra Ref radar reflector; R Bn radiobeacon; R TR radio tower; Rot rotating; s seconds; SEC sector; St M statute miles; VQ very quick; W white; WHIS whistle; Y yellow

Bottom characteristics:
Blds boulders; bk broken; Cy clay; Co coral; G gravel; Grs grass; gy gray; h hard; M mud; Oys oysters; Rk rock; S sand; so soft; Sh shells; sy sticky

Miscellaneous:
AUTH authorized; ED existence doubtful; Obstn obstruction; PA position approximate; PD position doubtful; Rep reported; Subm submerged
(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

HEIGHTS
Heights in feet above Mean High Water.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.366″ northward and 1.787″ eastward to agree with this chart.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

Nautical Miles 0
Yards 500 0 500 1000 1500

FISH TRAP AREAS
Boundary lines of fish trap areas are shown thus: — — —
Submerged piling may exist in these areas.

PLANE COORDINATE GRID
(based on NAD 1927)
Rhode Island State Grid is indicated by dotted ticks at 5000 foot intervals.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 2 for important supplemental information.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

CAUTION
Only marine radiobeacons have been calibrated for surface use. Limitations on the use of certain other radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light List and Defense Mapping Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

POINT JUDITH HARBOR OF REFUGE AND POND
CORPS OF ENGINEERS REPORTS TO APRIL 1986
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOW WATER (MLW)

NAME OF CHANNEL	DEPTH MLW (FEET)	WIDTH (FEET)	DATE OF SURVEY
CHANNEL ENTRANCE (41°21′58″N., 71°30′53″W.) TO THE STATE PIER AT JERUSALEM	11.5	150	2-83
EAST BRANCH CHANNEL	11.2	225-150	2-83
CHANNEL BUOY 6 (41°23′33″N., 71°30′49″W.) TO BUOY 11	4.8	100	12-85
BASIN ENTRANCE (41°25′14″N., 71°29′50″W.) TO TURNING BASIN	5.9	100	12-85
TURNING BASIN	5.2	400	12-85

NOTE-CONSULT THE CORPS OF ENGINEERS FOR CHANGING CONDITIONS SUBSEQUENT TO THE ABOVE
PRODUCED BY COMPUTER ASSISTED METHODS

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOAA VHF-FM WEATHER BROADCASTS
The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

New London, CT	KHB-47	162.55 MHz
Providence, RI	WXJ-39	162.55 MHz

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:
Pipeline Area — Cable Area
Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CRF 153).

SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Charted hydrography may originate from these and prior surveys.

SOURCE

a 1948,61	NOS Surveys	1:10,000
b 1956	NOS Surveys	1:12,500
c 1983-85	Corps of Engineers Surveys	
d 1991	NOS Surveys	1:10,000

(CONTINUED ON CHART 13221)
(CONTINUED ON CHART 13218)
(CONTINUED ON CHART 13218)
(CONTINUED ON CHART 13216)
(CONTINUED ON CHART 13216)
(CONTINUED ON CHART 13220)

FATHOMS / FEET / METERS

ED. NO. 10

DMA STOCK NO. 13XHA13219

10th Ed., Apr. 27/96 ■
13219

CAUTION
This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard District to the date shown in the lower left hand corner.

SOUNDINGS IN FEET

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

(Point Judith Harbor)
SOUNDINGS IN FEET - SCALE 1:15,000

13219