



# Modeling C-Band Co-Channel Interference From AeroMACS Omni-Directional Antennas to Mobile Satellite Service Feeder Uplinks

*Jeffrey D. Wilson*  
*Glenn Research Center, Cleveland, Ohio*

## NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA STI Help Desk at 443-757-5803
- Telephone the NASA STI Help Desk at 443-757-5802
- Write to:  
NASA Center for AeroSpace Information (CASI)  
7115 Standard Drive  
Hanover, MD 21076-1320

NASA/TM—2011-216938



# Modeling C-Band Co-Channel Interference From AeroMACS Omni-Directional Antennas to Mobile Satellite Service Feeder Uplinks

*Jeffrey D. Wilson*  
*Glenn Research Center, Cleveland, Ohio*

National Aeronautics and  
Space Administration

Glenn Research Center  
Cleveland, Ohio 44135

---

January 2011

## Acknowledgments

The author thanks John Pahl of Transfinite Systems Limited for help with the Visualyse Professional software, Dr. Izabela Gheorghisor of The MITRE Corporation for sharing her airport data set, Robert Kerczewski and James Budinger of NASA for helpful discussions and comments, and Rafael Apaza of the Federal Aviation Administration for helpful discussions and support.

This report contains preliminary findings,  
subject to revision as analysis proceeds.

Trade names and trademarks are used in this report for identification  
only. Their usage does not constitute an official endorsement,  
either expressed or implied, by the National Aeronautics and  
Space Administration.

*Level of Review:* This material has been technically reviewed by technical management.

Available from

NASA Center for Aerospace Information  
7115 Standard Drive  
Hanover, MD 21076-1320

National Technical Information Service  
5301 Shawnee Road  
Alexandria, VA 22312

Available electronically at <http://gltrs.grc.nasa.gov>

# **Modeling C-Band Co-Channel Interference From AeroMACS Omni-Directional Antennas to Mobile Satellite Service Feeder Uplinks**

Jeffrey D. Wilson  
National Aeronautics and Space Administration  
Glenn Research Center  
Cleveland, Ohio 44135

## **Summary**

A new C-band (5091 to 5150 MHz) airport communications system designated as Aeronautical Mobile Airport Communications System (AeroMACS) is being planned under the Federal Aviation Administration's NextGen program. An interference analysis software program, Visualyse Professional (Transfinite Systems Ltd), is being utilized to provide guidelines on limitations for AeroMACS transmitters to avoid interference with other systems. A scenario consisting of a single omni-directional transmitting antenna at each of the major contiguous United States airports is modeled and the steps required to build the model are reported. The results are shown to agree very well with a previous study.

## **1.0 Introduction**

Aeronautical Mobile Airport Communications System (AeroMACS) is a new C-band (5091 to 5150 MHz) airport communications system being planned under the Federal Aviation Administration's NextGen program (Ref. 1). Radio Technical Commission for Aeronautics (RTCA) Special Committee 223 is now engaged in defining standards for the AeroMACS service in the United States. European Organization for Civil Aviation Equipment (EUROCAE) Working Group 82 is conducting a parallel activity in Europe. It is essential that significant interference with other C-band systems already occupying the band does not occur. Services for which approved allocations now exist in the 5091 to 5150 MHz band include Aeronautical Radionavigation Service (ARNS), Aeronautical Mobile Service (AMS) (specifically Aeronautical Security (AS)), Aeronautical Mobile Telemetry (AMT), Aeronautical Mobile (Route) Service (AM(R)S), and Fixed Satellite Service (FSS) (specifically Mobile Satellite Service (MSS) feeder uplink). The Globalstar low Earth orbit (LEO) constellation is currently using the FSS service allocation in this band. The other services allocated in this band are not yet being used. At the same time, the AeroMACS system will operate as AM(R)S, with a higher priority than the other services allocated except the incumbent FSS system. Hence, the issue of primary and immediate interest is interference from AeroMACS into the FSS, specifically the MSS feeder uplink. The ultimate goal of this effort is to enable the establishment of practical limits on AeroMACS transmissions from airports so that the threshold of interference into MSS is not exceeded. The limits thus established will be used in the RTCA standards development process.

## **2.0 Analysis**

In this interference modeling of a simplified AeroMACS architecture, Visualyse Professional Version 7 software from Transfinite Systems Limited (United Kingdom) (Ref. 2) is utilized. In order to benchmark the software, the architecture configuration of a case from Hoh, Gheorghisor and Box (Ref. 3) is used in the model and the results compared. In Reference 3, the co-channel interference from an Airport Network and Location Equipment (ANLE/now referred to as AeroMACS) system to non-geostationary mobile-satellite-service (MSS) feeder uplinks was analyzed. It was assumed that there was

one transmitter with an omni-directional antenna at each of 497 major airports in the contiguous United States. A worst case scenario was modeled with all transmitters on 100 percent of the time.

In the model, each airport transmitting antenna contributes the interference power  $P_r$  at the LEO, 1414 km above the surface:

$$P_r(\text{dBW}) = P_t + G_t - L_c + G_r - L_{\text{free}}(d) - L_{\text{feed}} - L_p + B_f \quad (1)$$

where

- $P_t$  transmitter power = 8.6 dBW (7.2 W)
- $G_t$  AeroMACS antenna gain (8 dBi peak)
- $L_c$  cable/line loss in AeroMACS transmission system = 1 dB
- $G_r$  satellite antenna gain (6 dBi peak)
- $L_{\text{free}}$  free-space path loss (dB)
- $L_{\text{feed}}$  feed loss = 2.9 dB
- $L_p$  polarization discrimination = 1 dB
- $B_{\text{LEO}}$  receiver bandwidth at LEO satellite = 1.23 MHz
- $B_{\text{AER}}$  transmitter bandwidth at AeroMACS ground station = 20 MHz
- $B_f$  bandwidth factor =  $10 \cdot \log(B_{\text{LEO}}/B_{\text{AER}}) = -12.1$  dB
- $d$  distance between AeroMACS transmitter and LEO satellite receiver (1414+ km)

The components of the model consist of antennas, stations, carriers, links, and interference paths. The details of building these components into the model are indicated below.

## 2.1 Antennas

### 2.1.1 Globalstar Antenna

From Reference 3, the Globalstar (LEO-D) satellite has a  $100.9^\circ$  field of view (FOV) which enables it to cover approximately 9% of the Earth's surface. Its receiving antenna has a maximum gain of 6 dBi at a nadir angle of  $45^\circ$ .

To model this antenna, the antenna submenu is selected and an antenna named 'Globalstar antenna' is entered (Fig. 1). The 'Edit' button is clicked, a circular beam is selected, and the 'Change' button is clicked. The following gain table (Fig. 2) is entered and the gain distribution is shown graphically in Figure 3.




Figure 1.—Naming Globalstar antenna in Antenna submenu.




Figure 2.—Entering Globalstar receiving antenna gain distribution.




Figure 3.—Globalstar (LEO-D) satellite receiving antenna gain.

### 2.1.2 Omni-Directional Antenna (for AeroMACS Base Stations)

For this antenna, the gain pattern as a function of elevation angle is given in ITU-RF.1336-1 (Ref. 4) with maximum gain  $G_0=8$  and

$$G(\theta) = \max[G_1(\theta), G_2(\theta)] \quad (2a)$$

$$G_1(\theta) = G_0 - 12 \left( \frac{\theta}{\theta_3} \right)^2 \quad (2b)$$

$$G_2(\theta) = G_0 - 12 + 10 \log \left[ \left( \max \left\{ \frac{|\theta|}{\theta_3}, 1 \right\} \right)^{-1.5} + k \right] \quad (2c)$$

where

- $G(\theta)$  gain relative to an isotropic antenna (dBi),
- $G_0$  the maximum gain in or near the horizontal plane (dBi),
- $\theta$  absolute value of the elevation angle relative to the angle of maximum gain (degrees),

$\theta_3$  the 3 dB beamwidth in the vertical plane (degrees), and  
 $k$  parameter which accounts for increased side-lobe levels above what would be expected for an antenna with improved side-lobe performance.

The relationship between the gain (dBi) and the 3 dB beamwidth in the elevation plane (degrees) is:

$$\theta_3 = 107.6 \times 10^{-0.1 G_0} \quad (2d)$$

In cases involving typical antennas operating in the 1 to 3 GHz range, the parameter  $k$  should be 0.7 (Ref. 4). The corresponding antenna gain as a function of elevation angle is shown in Figure 4. A shaped beam is selected in the Antenna Properties for the Omni-Directional Antenna. Equation (2a) is input into a Microsoft Excel (Microsoft Corporation) spreadsheet and the output is entered into the Elevation/Azimuth table shown in Figure 5.




Figure 4.—Omni-directional AeroMACS base station antenna gain as a function of elevation angle.




Figure 5.—Entering elevation gain pattern for base station omnidirectional antenna.

## 2.2 Stations and Station Groups

Stations identify the locations of the transmitters and receivers. In the Station submenu (Fig. 6), a Globalstar (G\*) satellite is added and through the Select Station Type submenu is defined to be a Terrestrial Fixed station. The position of a Globalstar satellite was then defined. The latitude and longitude were arbitrarily chosen and the altitude was defined to be that of the Globalstar orbits, 1414 km (Fig. 7). The Globalstar satellite was then linked to the previously defined Globalstar antenna (Fig. 8). A feeder loss of 2.9 dB was entered corresponding to the value in Table 3-2 of Reference 3. Because a Terrestrial Fixed Station was used to represent a satellite, the elevation needed to be set to  $-90^\circ$ . One of the 497 airport base stations was also defined to be a Terrestrial Fixed Station and identified as Custom-2-2-1 (Fig. 9). Its latitude and longitude were entered and a height above terrain of 20 ft (6.096 m) was defined. Its antenna was linked to the omni-directional antenna previously defined (Fig. 10). This station is used as a template for the other 496 airport base station transmitters through the wizard in the Stations Groups submenu (Fig. 11). The latitudes and longitudes of the other base stations are entered through reading a comma-separated values (csv) file (Fig. 12). This results in a Station List of  $1+497 = 498$  stations (Fig. 13). In the Station Groups submenu, the airport base stations are linked together as 'Locations Service Area' (Fig. 14).



Figure 6.—Station types.



Figure 7.—Setting the position of a Globalstar satellite.



Figure 8.—Linking Globalstar satellite to Globalstar antenna.



Figure 9.—Defining the position of the first airport base station.




Figure 10.—Linking the first airport base station to the omni-directional antenna.




Figure 11.—Defining the first airport base station as a template.




Figure 12.—The latitudes and longitudes of the other 496 airport base stations are entered.




Figure 13.—List of stations include a Globalstar satellite and 497 airport base stations.




Figure 14.—The airport base stations are linked together as 'Locations Service Area'.

## 2.3 Carriers

The carrier submenu is used to designate bandwidths, polarization, and other characteristics of the signal spectrum. The AeroMACS carrier with 20 MHz bandwidth and Globalstar carrier with 1.23 MHz bandwidth are defined in Figures 15 and 16.




Figure 15.—Defining AeroMACS carrier.




Figure 16.—Defining Globalstar carrier.

## 2.4 Links

Links are used to connect stations, define propagation parameters, and criteria for interference levels. A link defines a communications path. In this model, transmit links are defined from the airport transmitters and a receive link is defined at the Globalstar satellite. Transmitter links are defined for each of the 497 airport base stations in the 'Locations Service Area' (Fig. 17), each utilizing the previously defined AeroMACS carrier at 5.1 GHz with a transmitter power of 8.6 dBW (7.24 W). In Reference 3, it is assumed that there is 1 dB of line losses at the transmitters, so the transmit link power is set to 7.6 dBW (Fig. 18). The receiver link is defined at the Globalstar satellite (Fig. 19) and utilizes the Globalstar carrier at 5.1 GHz (Fig. 20).




Figure 17.—Setting up transmit links at each of the airport base stations.




Figure 18.—The transmit links utilize the AeroMACS carrier at 5.1 GHz with a transmitter power of 8.6 dBW. (In Ref. 3, it is assumed that there is 1 dB of line losses at the transmitters, so the transmit link power is set to 7.6 dBW.)




Figure 19.—Receive link defined at Globalstar satellite.




Figure 20.—Receive link utilizes Globalstar carrier.

All the links are defined as type 'Earth <-> Space'. Other types in Visualyse are Terrestrial Fixed, Terrestrial Mobile, Space <-> Space, and Broadcasting. With this type we can choose from a number of propagation models. The model ITU-R Rec. P.525, Basic Transmission Loss in Free Space (Ref. 5), is selected from the window below (Fig. 21).




Figure 21.—Basic Transmission Loss in Free Space propagation model selected.

## 2.5 Interference Paths

An interference path consists of a wanted or ‘victim’ link and an unwanted or ‘interfering’ link or links (Fig. 22). In this case the interference path is designated as ‘Airports into G\*’ to represent the Globalstar receive link as the victim link and the transmit links at each of the AeroMACS airport base stations as the interfering links (Fig. 23).



Figure 22.—Designating the Globalstar receive link as the ‘wanted’ link.




Figure 23.—Designating the transmit links at each of the AeroMACS airport base stations as the interfering links.

## 2.6 Output Menu

In order to plot the interference power over a map of the Western Hemisphere, the Create Area Analysis submenu is selected from the Output Menu and the following coordinates, station, link, and plot parameter are entered. The plot resolution is set to 175.74 km which provides 2° of longitude resolution (Fig. 24).

**Area Analysis Properties**

Name:

**Area Coordinates**

Top:  Right:   
Left:  Bottom:

**Moving Station**

Station:

**Plot parameter**

Link:

- + Components of the link calculation
- + Antenna pointing
- + Worst interfering signal
- + Single entry interference
- Aggregate interference
- I**
- I/N
- C/I

Current  Minimum  Maximum  Mean

**Plotting Options**

Contour plot  Colour block plot

Plot resolution:  
At least:  km (between test points)

Suspend drawing for faster updates

Figure 24.—Setting up the output map of interference power.

### 3.0 Results

The simulated interference power is shown in global view in Figure 25. The corresponding two-dimensional view is shown in Figure 26.




Figure 25.—Simulated interference power in global view.




Figure 26.—Simulated interference power in two-dimensional view.

The agreement is excellent between the Visualyse simulated interference power distribution shown in Figure 26 and that calculated by Hoh, et al. in Reference 3. In the Visualyse model, the maximum interference power is  $-149.3$  dBW at the location  $64^\circ$  N  $105^\circ$  W, which compares well with the value of  $-150.0$  dBW in Reference 3 at the location  $67^\circ$  N  $104^\circ$  W. This maximum interference power over northern Canada is due to the maximum transmitting gain of the AeroMACS antennas in the horizontal direction.

## 4.0 Conclusions

The software program Visualyse Professional has been used to model a simplified architecture for the proposed Aeronautical Mobile Airport Communications System (AeroMACS). The model scenario consisted of a single omni-directional transmitting antenna at each of the 497 major contiguous United States airports. The AeroMACS transmitter power was chosen to be the same as a previous study in order to verify the model. Details of the model building were described and the results agreed closely to that of the previous study in which the interference power over almost all of North America exceeds the desired threshold. This agreement provides confidence that the model is accurate and serves as a starting point for developing and investigating more sophisticated and realistic AeroMACS scenarios.

## References

1. W. Ward, J. Budinger, R. Dimond, J. Wilson, and R. Apaza, "Aeronautical Mobile Airport Communications System Development Status," IEEE 2010 Integrated Communications, Navigation and Surveillance Conference, May 11–13, 2010.
2. Transfinite Systems Ltd, <http://www.transfinite.com/>.
3. Y.-S. Hoh, I.L. Gheorghisor, and F. Box, "Feasibility Analysis of 5091-5150 MHz Band Sharing by ANLE and MSS Feeder Links," MITRE-CAASD Report MP 05W0000083, 2005.
4. Recommendation ITU-R F.1336-1, "Reference Radiation Patterns of Omnidirectional, Sectoral and other Antennas in Point-to-Multipoint Systems for Use in Sharing Studies in the Frequency Range from 1 GHz to about 70 GHz," 1997–2000.
5. Recommendation ITU-R P.525-2, "Calculation of Free-Space Attenuation," 1978–1994.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
<b>1. REPORT DATE (DD-MM-YYYY)</b> 01-01-2011		<b>2. REPORT TYPE</b> Technical Memorandum		<b>3. DATES COVERED (From - To)</b>	
<b>4. TITLE AND SUBTITLE</b> Modeling C-Band Co-Channel Interference From AeroMACS Omni-Directional Antennas to Mobile Satellite Service Feeder Uplinks			<b>5a. CONTRACT NUMBER</b>		
			<b>5b. GRANT NUMBER</b>		
			<b>5c. PROGRAM ELEMENT NUMBER</b>		
<b>6. AUTHOR(S)</b> Wilson, Jeffrey, D.			<b>5d. PROJECT NUMBER</b>		
			<b>5e. TASK NUMBER</b>		
			<b>5f. WORK UNIT NUMBER</b> WBS 031102.02.03.02.0677.09		
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b> E-17542		
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> National Aeronautics and Space Administration Washington, DC 20546-0001			<b>10. SPONSORING/MONITOR'S ACRONYM(S)</b> NASA		
			<b>11. SPONSORING/MONITORING REPORT NUMBER</b> NASA/TM-2011-216938		
<b>12. DISTRIBUTION/AVAILABILITY STATEMENT</b> Unclassified-Unlimited Subject Category: 04 Available electronically at <a href="http://gltrs.grc.nasa.gov">http://gltrs.grc.nasa.gov</a> This publication is available from the NASA Center for AeroSpace Information, 443-757-5802					
<b>13. SUPPLEMENTARY NOTES</b>					
<b>14. ABSTRACT</b> A new C-band (5091 to 5150 MHz) airport communications system designated as Aeronautical Mobile Airport Communications System (AeroMACS) is being planned under the Federal Aviation Administration's NextGen program. An interference analysis software program, Visualyse Professional (Transfinite Systems Ltd), is being utilized to provide guidelines on limitations for AeroMACS transmitters to avoid interference with other systems. A scenario consisting of a single omni-directional transmitting antenna at each of the major contiguous United States airports is modeled and the steps required to build the model are reported. The results are shown to agree very well with a previous study.					
<b>15. SUBJECT TERMS</b> Airports; Transmitters; Low Earth orbits; Bandwidth; Omnidirectional antennas; C-band; Mobile communications systems					
<b>16. SECURITY CLASSIFICATION OF:</b>			<b>17. LIMITATION OF ABSTRACT</b>	<b>18. NUMBER OF PAGES</b>	<b>19a. NAME OF RESPONSIBLE PERSON</b>
<b>a. REPORT</b> U	<b>b. ABSTRACT</b> U	<b>c. THIS PAGE</b> U			STI Help Desk (email:help@sti.nasa.gov)
			UU	23	<b>19b. TELEPHONE NUMBER (include area code)</b> 443-757-5802



