Formerly C&GS 212, 1st Ed., Feb. 1960

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

SOUNDINGS IN FEET

Nautical Chart Catalog No. 1, Panel H

LITIGATION/COPY

UNITED STATES – EAST COAST
MAINE – NEW HAMPSHIRE
PORTSMOUTH TO DOVER AND EXETER

Mercator Projection
Scale 1:20,000 at Lat. 43°06′
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

TIDAL INFORMATION

Place		Height referred to datum of soundings (MLLW)			
Name	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
		feet	feet	feet	feet
Portsmouth	(43°05′N/70°45′W)	8.5	8.1	0.3	-3.5
Dover Point	(43°07′N/70°50′W)	7.0	6.6	0.2	-3.0
Salmon Falls River Entrance	(43°11′N/70°50′W)	7.4	7.1	0.3	-3.0
Squamscott River R.R. Bridge	(43°03′N/70°55′W)	4.7	7.1	0.2	-3.0

(490)

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

NOAA VHF-FM WEATHER BROADCASTS
The National Weather Service stations listed below provide continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Portland, Maine	KDO-95	162.55 MHz
Boston, Mass.	KHB-35	162.475 MHz

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 1 for important Supplemental information.

CAUTION
Only marine radiobeacons have been calibrated for surface use. Limitations on the use of certain other radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and Defense Mapping Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio tower
Al alternating	Gp group	N nun	Rot rotating
B black	IQ interrupted quick	OBSC obscured	s seconds
Bn beacon	Iso isophase (E Int)	Oc occulting	SEC sector
C can	LT HO lighthouse	Or orange	St M statute miles
DIA diaphone	M nautical mile	Q quick	VQ very quick
E Int equal interval (Iso)	m minutes	R red	W white
F fixed	MICRO TR microwave tower	Ra Ref radar reflector	WHIS whistle
Fl flashing	Mkr marker	R Bn radiobeacon	Y yellow

Bottom characteristics:

Blds boulders	Co coral	gy gray	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky

Miscellaneous:

AUTH authorized	Obstn obstruction	PD position doubtful	Subm submerged
ED existence doubtful	PA position approximate	Rep reported	

21 Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

HEIGHTS
Heights in feet above Mean High Water.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Charting and Geodetic Services with additional data from the Corps of Engineers and U.S. Coast Guard.

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the Nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.316″ northward and 1.802″ eastward to agree with this chart.

LOGARITHMIC SPEED SCALE
To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots

DMA STOCK NO. 13BHA13285

8th Ed., Nov. 3/90

CAUTION
This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner.

SOUNDINGS IN FEET

LITIGATION/COPY

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Director, Charting and Geodetic Services (N/CG22), National Ocean Service, NOAA, Rockville, Maryland 20852.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE

20th Anniversary 1970–1990
National Oceanic and Atmospheric Administration
"Serving The Nation"
John A. Knauss Administrator

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FEET	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102

METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

(Portsmouth to Dover and Exeter)
SOUNDINGS IN FEET - SCALE 1:20,000